TWIST ROLLERS

Transport Mode (Closed)

Working Mode (Opened)

1. Hydraulic Transport Wheels
2. Hydraulic Drawbar Swivel
3. Adjustable Drawbar

Model	Working Width	Roller Diameter	Transport Width	Weight	Roller Thickness
TR2012	6.1m (20')	1020mm (40")	2.5m	2.5 - 4.5T	12, 16 or 25mm

Specs are approximate and subject to change

Custom widths and roller sizes are available by special order

FLATOUT TWIST ROLLER

OzValue AG MACHINERY

MORE COMMITMENT LESS MONEY

Now more than ever, farming in Australia has become highly dependent on machinery cost and reliability. This is why OzValue Ag is committed to bringing the farmers of Australia, well priced quality machinery.

With an ever expanding range, the team at OzValue Ag is continuing to introduce such equipment to Australia. OzValue Ag is able to source machinery from manufacturers around the world and sell direct to the farmer eliminating importers and distributors.

Put simply this all results in a lower price for the Farmer.

FLATOUT LAND ROLLERS

LAND ROLLERS

OzValue AG MACHINERY

OzValue AG Victoria
6 Wiltshite Lane. Delacombe (Ballarat) VIC 3350
P. 03 5335 8181
E. info@ozvalueag.com.au

ozvalueag.com.au

OzValue AG MACHINERY

FIXED ROLLERS

1. 75mm Bearings
2. Adjustable Drawbar
3. Removable Drawbar

Model	Working Width	Roller Diameter	Transport Width	Weight	Roller Thickness
FR1012	3.0m (10')	1020mm (40")	3.3m	1.2 - 2.4T	12, 16 or 25mm
FR1212	3.6m (12')	1020mm (40")	3.9m	1.4 - 2.6T	12, 16 or 25mm
FR1412	4.2m (14')	1020mm (40")	4.5m	1.6 - 2.9T	12, 16 or 25mm

Specs are approximate and subject to change

Custom widths and roller sizes are available by special order

TRI-PLEX ROLLERS

MORE ROLLER. LESS MONEY.

With machinery costs increasing, Oz Value Ag offers Land Rollers at a more affordable price than ever. The simple robust design, allows the machine to stay in the field when it is most needed. 75mm bearings and an RHS frame are just some of the features of this machine. Drum options consist of 12mm, 16mm and 25mm offering ground pressures up to 1000kg per meter, ideal for rolling lentils, peas and beans. The three section design of the Tri-Plex Roller provides an even roll with overlap in between each of the rollers.

Model	Working Width	Roller Diameter	Transport Width	Weight	Roller Thickness
TP3012	9.1m (30')	1020mm (40")	4.1m	6.5 - 9.7T	12, 16 or 25mm
TP4012	12.4m (40'8")	1020mm (40")	4.1m	7.6 - 11.5T	12, 16 or 25mm
TP5012	15.2m (50')	1020mm (40")	4.1m	9.1 - 14.1T	12, 16 or 25mm
TP6012	18.2m (60')	1020mm (40")	6.1m	12.6 - 18.9T	12, 16 or 25mm

Specs are approximate and subject to change

Custom widths and roller sizes are available by special order

1. Hydraulic Locking Mechanism
2. 4.1m Transport Width
3. Floating Drawbar

4. Twin Lock Mechanism
5. Dual Rear Wheels
6. Hydraulic Steering Rear Wheels

FLATOUT FIXED ROLLER

FLATOUT TRI-PLEX ROLLER